NSN 5930-01-038-7946

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-038-7946

Overall Length:
4.250 inches
Overall Height:
6.230 inches
Body Height:
3.100 inches
Longest Horizontal Distance Between Mounting Centers:
4.250 inches
Longest Vertical Distance Between Mounting Centers:
3.100 inches
Pressure Switch Type:
Gage
Mounting Method:
Bracket
Features Provided:
Electrical box connector
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
4500.00 pounds per square inch
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Four position rectangular
Nonpile-up Contact Arrangement:
5 two circuit, double break/double make, both positions maintained
Terminal Type:
Solder stud
Contact Load Current Rating:
6.0 amperes resistive load fourth voltage and 5.0 amperes inductive load fourth voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+350.00/+675.00 actuation point pounds per square inch and +350.00/+625.00 deactuation point pounds per square inch
Contact Adjustment Type:
Internal deactuation point screw and internal actuation point screw
Contact Stimulus Rating:
50.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level fourth voltage

NSN 5930-01-038-7946

Pressure Switch - Page 2 of 2



Pressure Connector T	ype
----------------------	-----

Gasket seal, threaded external single connection

Media For Which Designed:

Gas or liquid

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A048b0