

View Online at <https://aerobasegroup.com/nsn/5930-01-038-7946>

Overall Length:

4.250 inches

Overall Height:

6.230 inches

Body Height:

3.100 inches

Longest Horizontal Distance Between Mounting Centers:

4.250 inches

Longest Vertical Distance Between Mounting Centers:

3.100 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket

Features Provided:

Electrical box connector

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

4500.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

5 two circuit, double break/double make, both positions maintained

Terminal Type:

Solder stud

Contact Load Current Rating:

6.0 amperes resistive load fourth voltage and 5.0 amperes inductive load fourth voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+350.00/+675.00 actuation point pounds per square inch and +350.00/+625.00 deactuation point pounds per square inch

Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

Contact Stimulus Rating:

50.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level fourth voltage

Pressure Connector Type:

Gasket seal, threaded external single connection

Media For Which Designed:

Gas or liquid

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiiq:

A048b0