

View Online at <https://aerobasegroup.com/nsn/5930-01-038-8773>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Moisture proof

**Body Length:**

1.120 inches

**Body Width:**

0.870 inches

**Body Height:**

2.440 inches

**Actuator Length:**

Between 1.002 inches and 1.007 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.290 inches

**Actuator Width:**

Between 0.752 inches and 0.757 inches

**Actuator Color:**

White single actuator

**Illuminated Actuator Color:**

White single actuator

**Actuator Inscription:**

Log normal, lin normal single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes resistive dc and 1.000 amperes inductive dc and 750.000 milliamperes lamp dc and 2.000 amperes resistive ac and 1.000 amperes inductive ac and 750.000 milliamperes lamp ac

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0