

View Online at <https://aerobasegroup.com/nsn/5930-01-038-8779>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Moisture proof

Body Length:

1.120 inches

Body Width:

0.870 inches

Body Height:

2.440 inches

Actuator Length:

Between 1.002 inches and 1.007 inches

Actuator Style:

Rectangular

Actuator Height:

0.290 inches

Actuator Width:

Between 0.752 inches and 0.757 inches

Actuator Color:

Gray single actuator and white single actuator

Illuminated Actuator Color:

Gray single actuator and white single actuator

Actuator Inscription:

Radiate complete, radiate initiate single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.000 amperes inductive dc and 750.000 milliamperes lamp dc and 2.000 amperes resistive ac and 1.000 amperes inductive ac and 750.000 milliamperes lamp ac

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0