NSN 5930-01-038-9690

Push Switch - Page 1 of 2

No



View Online at https://aerobasegroup.com/nsn/5930-01-038-9690

Body Style: Panel mount Hazardous Locations/environmental Protection: Moisture proof **Body Length:** 1.120 inches **Body Width:** 0.870 inches **Body Height:** 2.440 inches Actuator Length: Between 1.002 inches and 1.007 inches **Actuator Style:** Rectangular **Actuator Height:** 0.290 inches **Actuator Width:** Between 0.752 inches and 0.757 inches **Actuator Color:** White single actuator and yellow single actuator **Illuminated Actuator Color:** White single actuator and yellow single actuator **Actuator Inscription:** On, off single actuator Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc Inclosure Type: Fully enclosed **Mounting Method:** Panel Nonpile-up Contact Arrangement: 2 pole, double throw, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 2.000 amperes resistive dc and 1.000 amperes inductive dc and 750.000 milliamperes lamp dc and 2.000 amperes resistive ac and 1.000 amperes inductive ac and 750.000 milliamperes lamp ac **Terminal Type And Quantity:** 6 tab, solder lug Shelf Life: N/a Unit Of Measure: ---**Demilitarization:**

NSN 5930-01-038-9690

Push Switch - Page 2 of 2

Fiig: A053a0

