NSN 5930-01-039-3147

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-039-3147

Overall Length:
4.875 inches
Overall Height:
3.281 inches
Overall Width:
2.875 inches
Body Height:
2.500 inches
Capillary Tube Length:
300.0 inches
Longest Horizontal Distance Between Mounting Centers:
2.406 inches
Shortest Horizontal Distance Between Mounting Centers:
0.656 inches
Longest Vertical Distance Between Mounting Centers:
3.281 inches
Tempurature Sensing Element Type:
Capillary tube
Mounting Method:
Bracket
Features Provided:
Electrical access port
Contact Action Stimulus:
Decrease
Mounting Facility Pattern:
Isosceles triangle
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Tab w/screw
Contact Load Current Rating:
3.2 amperes resistive load first voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
-13.00/+63.00 actuation point degrees fahrenheit and -10.00/+60.00 deactuation point degrees fahrenheit
Contact Adjustment Type:
External deactuation point knob and external actuation point knob
Contact Voltage Rating In Volts:
550.0 ac at sea level first voltage
Media For Which Designed:

Gas or liquid

NSN 5930-01-039-3147

Thermostatic Switch - Page 2 of 2



Style Designator:
Rectangular
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A048b0