NSN 5930-01-039-3160

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-039-3160 **Body Style:** Hole mounted **Body Length:** 1.880 inches **Body Width:** 0.650 inches **Body Height:** 1.590 inches **Unthreaded Mounting Hole Diameter:** 0.138 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.000 inches **Actuator Style:** Round **Actuator Diameter:** 0.250 inches **Actuator Height:** 0.375 inches **Maximum Voltage Rating In Volts:** 250.0 ac and 28.0 dc Inclosure Type: Fully enclosed **Mounting Method:** Unthreaded hole **Nonpile-up Contact Arrangement:** 4 pole, double throw, both positions maintained single switch unit **Actuator Movement:** Between 0.172 pretravel inches and 0.078 overtravel inches and 0.250 differential inches **Contact Load Current Rating At Maximum Rated Voltage:** 5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac **Special Features:** 2 units, switches a and b operate on pull stroke of actuator rod, switch b operates on push stroke **Terminal Type And Quantity:** 12 tab, solder lug Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Fiig: A053a0

No