

View Online at <https://aerobasegroup.com/nsn/5930-01-039-3160>

**Body Style:**

Hole mounted

**Body Length:**

1.880 inches

**Body Width:**

0.650 inches

**Body Height:**

1.590 inches

**Unthreaded Mounting Hole Diameter:**

0.138 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

1.000 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.250 inches

**Actuator Height:**

0.375 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

4 pole, double throw, both positions maintained single switch unit

**Actuator Movement:**

Between 0.172 pretravel inches and 0.078 overtravel inches and 0.250 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

**Special Features:**

2 units, switches a and b operate on pull stroke of actuator rod, switch b operates on push stroke

**Terminal Type And Quantity:**

12 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0