

View Online at <https://aerobasegroup.com/nsn/5930-01-039-3771>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Bushing Length:

0.438 inches

Body Length:

0.572 inches

Body Width:

0.556 inches

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

0.687 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Trainer, b-1b aircraft; support equipment, b-52 aircraft; helicopter, advance attack, ah-1w; systems, jp-5 aviation fuels; ticonderoga class cg (47); virginia class cgn (41); sturgeon class ssn (637); los angles class ssn (688); aircraft, ac-130h, mc-130h, ec-130e, hc-130

Mounting Surface To Terminal End Distance:

0.706 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, two positions momentary single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 1.000 amperes inductive dc and 3.000 amperes resistive ac and 2.000 amperes inductive ac

Special Features:

Weapons system essential

Test Data Document:

96906-ms21353 standard (includes industry or association standards, individual manufactureer standards, etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Specification Data:

96906-ms21353-341 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0