

View Online at <https://aerobasegroup.com/nsn/5930-01-039-4572>

Body Style:

Bushing mounted

Body Length:

0.476 inches

Actuator Style:

Round

Actuator Diameter:

0.070 inches

Actuator Free Position Height:

0.028 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.437 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

30.0 ounces

Actuator Movement:

Between 0.009 pretravel inches and 0.003 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 3.000 amperes inductive dc and 2.000 amperes lamp dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac and 2.000 amperes lamp ac

Test Data Document:

81349-mils8805-68 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Specification Data:

81349--8805-68-002 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

A053a0