

View Online at <https://aerobasegroup.com/nsn/5930-01-039-6726>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Explosion proof

Bushing Length:

0.470 inches

Body Length:

0.650 inches

Body Width:

0.500 inches

Body Height:

0.415 inches

Actuator Style:

Round

Actuator Diameter:

0.240 inches

Actuator Height:

0.687 inches

Actuator Position-action Relationship:

Up position maintained and down position momentary

Actuator Color:

Natural single actuator

Maximum Voltage Rating In Volts:

20.0 ac and 20.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

3 pole, double throw, one position momentary single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

400.000 milliamperes resistive dc and 400.000 milliamperes resistive ac

Special Features:

Weapon system essential

Precious Material And Location:

Terminals gold and contact surfaces gold

Thread Series Designator:

Uns

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0