## NSN 5930-01-039-7130

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-039-7130 **Body Style: Bushing mounted Hazardous Locations/environmental Protection:** Humidity resistant **Bushing Length:** 0.250 inches **Body Length:** 0.770 inches **Case Material:** Metal **Actuator Diameter:** 0.125 inches **Actuator Height:** 0.304 inches **Actuator Color:** Black single actuator **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.250 inches **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 500.000 milliamperes resistive dc and 500.000 milliamperes resistive ac **Precious Material And Location:** Contact terminals silver **Thread Series Designator:** Unef **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5930-01-039-7130

Push Switch - Page 2 of 2



Fiig:

A053a0