

View Online at <https://aerobasegroup.com/nsn/5930-01-039-8391>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

5.750 inches

Overall Height:

10.938 inches

Overall Width:

3.000 inches

Body Width:

3.000 inches

Unthreaded Mounting Hole Diameter:

0.375 inches

Longest Horizontal Distance Between Mounting Centers:

3.000 inches

Shortest Horizontal Distance Between Mounting Centers:

1.062 inches

Longest Vertical Distance Between Mounting Centers:

4.250 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

3.2 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+500.00/+5000.00 actuation point pounds per square inch gage and +500.00/+5000.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

550.0 ac at sea level first voltage

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0