## NSN 5930-01-039-8392

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-039-8392

Inside Diameter:
0.250 inches single connection
Overall Length:
2.620 inches
Overall Height:
4.300 inches
Overall Width:
2.620 inches
Longest Horizontal Distance Between Mounting Centers:
2.120 inches
Longest Vertical Distance Between Mounting Centers:
2.120 inches
Pressure Switch Type:
Gage
Mounting Method:
Base
Features Provided:
Hermetically sealed case
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
120.00 pounds per square inch
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Four position rectangular
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary
Terminal Type:
Wire lead
Contact Load Current Rating:
5.0 amperes resistive load second voltage and 3.0 amperes inductive load second voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
7.00 actuation point inches of mercury and 6.00 deactuation point inches of mercury and 1.00 differential point inches of mercury
Contact Voltage Rating In Volts:
28.0 dc at sea level second voltage

Pressure Connector Type:

Gasket seal, threaded internal single connection

## NSN 5930-01-039-8392

Pressure Switch - Page 2 of 2



Frequency In Hertz:
50.0 first voltage and 60.0 first voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Cylindrical w/lugs
Thread Series Designator:
Npt single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A048b0