NSN 5930-01-039-8396

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-039-8396

Body Style:
Bushing mounted
Hazardous Locations/environmental Protection:
Dustproof
Body Diameter:
1.500 inches
Bushing Length:
0.657 inches
Body Length:
1.150 inches
Case Material:
Metal
Actuator Style:
Roller plunger
Actuator Free Position Height:
1.781 inches
Actuator Roller Diameter:
0.500 inches
Actuator Roller Width:
0.120 inches
Maximum Voltage Rating In Volts:
28.0 dc
28.0 dc
28.0 dc Inclosure Type:
28.0 dc Inclosure Type: Fully enclosed
28.0 dc Inclosure Type: Fully enclosed Switch Release Force:
28.0 dc Inclosure Type: Fully enclosed Switch Release Force: 32.0 ounces
28.0 dc Inclosure Type: Fully enclosed Switch Release Force: 32.0 ounces Switch Actuating Force:
28.0 dc Inclosure Type: Fully enclosed Switch Release Force: 32.0 ounces Switch Actuating Force: Between 48.0 ounces and 96.0 ounces
28.0 dc Inclosure Type: Fully enclosed Switch Release Force: 32.0 ounces Switch Actuating Force: Between 48.0 ounces and 96.0 ounces Actuator Movement:
28.0 dc Inclosure Type: Fully enclosed Switch Release Force: 32.0 ounces Switch Actuating Force: Between 48.0 ounces and 96.0 ounces Actuator Movement: Between 0.040 pretravel inches and 0.250 overtravel inches and 0.030 differential inches
28.0 dc Inclosure Type: Fully enclosed Switch Release Force: 32.0 ounces Switch Actuating Force: Between 48.0 ounces and 96.0 ounces Actuator Movement: Between 0.040 pretravel inches and 0.250 overtravel inches and 0.030 differential inches Terminal Type And Quantity:
Inclosure Type: Fully enclosed Switch Release Force: 32.0 ounces Switch Actuating Force: Between 48.0 ounces and 96.0 ounces Actuator Movement: Between 0.040 pretravel inches and 0.250 overtravel inches and 0.030 differential inches Terminal Type And Quantity: 9 wire lead
28.0 dc Inclosure Type: Fully enclosed Switch Release Force: 32.0 ounces Switch Actuating Force: Between 48.0 ounces and 96.0 ounces Actuator Movement: Between 0.040 pretravel inches and 0.250 overtravel inches and 0.030 differential inches Terminal Type And Quantity: 9 wire lead Shelf Life:
28.0 dc Inclosure Type: Fully enclosed Switch Release Force: 32.0 ounces Switch Actuating Force: Between 48.0 ounces and 96.0 ounces Actuator Movement: Between 0.040 pretravel inches and 0.250 overtravel inches and 0.030 differential inches Terminal Type And Quantity: 9 wire lead Shelf Life: N/a
28.0 dc Inclosure Type: Fully enclosed Switch Release Force: 32.0 ounces Switch Actuating Force: Between 48.0 ounces and 96.0 ounces Actuator Movement: Between 0.040 pretravel inches and 0.250 overtravel inches and 0.030 differential inches Terminal Type And Quantity: 9 wire lead Shelf Life: N/a
28.0 dc Inclosure Type: Fully enclosed Switch Release Force: 32.0 ounces Switch Actuating Force: Between 48.0 ounces and 96.0 ounces Actuator Movement: Between 0.040 pretravel inches and 0.250 overtravel inches and 0.030 differential inches Terminal Type And Quantity: 9 wire lead Shelf Life: N/a Unit Of Measure:
28.0 dc Inclosure Type: Fully enclosed Switch Release Force: 32.0 ounces Switch Actuating Force: Between 48.0 ounces and 96.0 ounces Actuator Movement: Between 0.040 pretravel inches and 0.250 overtravel inches and 0.030 differential inches Terminal Type And Quantity: 9 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: