

View Online at <https://aerobasegroup.com/nsn/5930-01-039-8397>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Body Length:

0.781 inches

Body Width:

0.250 inches

Body Height:

0.359 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

Between 0.087 inches and 0.090 inches

Actuator Length:

0.094 inches

Actuator Style:

Rectangular

Actuator Width:

0.094 inches

Actuator Free Position Height:

0.570 inches

Maximum Voltage Rating In Volts:

250.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

45.0 grams

Switch Actuating Force:

65.0 grams

Actuator Movement:

Between 0.141 pretravel inches and 0.030 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.100 amperes resistive ac

Special Features:

Auxiliary actuator with roller available in white nickel plated cold-rolled steel 0.406 in. Lg

Precious Material And Location:

Contacts silver and terminals silver

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0