

View Online at <https://aerobasegroup.com/nsn/5930-01-039-8397>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.375 inches

**Body Length:**

0.781 inches

**Body Width:**

0.250 inches

**Body Height:**

0.359 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

Between 0.087 inches and 0.090 inches

**Actuator Length:**

0.094 inches

**Actuator Style:**

Rectangular

**Actuator Width:**

0.094 inches

**Actuator Free Position Height:**

0.570 inches

**Maximum Voltage Rating In Volts:**

250.0 ac

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

45.0 grams

**Switch Actuating Force:**

65.0 grams

**Actuator Movement:**

Between 0.141 pretravel inches and 0.030 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.100 amperes resistive ac

**Special Features:**

Auxiliary actuator with roller available in white nickel plated cold-rolled steel 0.406 in. Lg

**Precious Material And Location:**

Contacts silver and terminals silver

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0