NSN 5930-01-039-9022

Pressure Switch - Page 1 of 2

Inside Diameter:

Overall Length:
4.130 inches
Overall Height:
4.190 inches
Overall Width:
3.500 inches

Mounting Slot Width:

0.280 inches **Body Height:**

0.250 inches single connection



View Online at https://aerobasegroup.com/nsn/5930-01-039-9022

2.250 inches	
Distance Between Mounting Facility Centers:	
2.500 inches	
Pressure Switch Type:	
Gage	
Mounting Method:	
Slot	
Features Provided:	
Electrical box connector	
Thready Qty Per Inch (tpi):	
18 single pressure connection	
Contact Action Stimulus:	
Increase	
Proof Pressure:	
97.00 inches of water	
Thread Size:	
0.250 inches single pressure connection	
Mounting Facility Pattern:	
Two position in-line	
Nonpile-up Contact Arrangement:	
2 pole, double throw, one position momentary	
Terminal Type:	
Wire lead	
Contact Load Current Rating:	
1.0 amperes resistive load first voltage	
Contact Adjustability:	
Deactuation point adjustable and actuation point adjustable	
Contact Adjustment Range:	
+2.00/+36.00 actuation point inches of water and +1.50/+34.70 deactuation point inches of water	r
Contact Adjustment Type:	
Internal deactuation point screw and internal actuation point screw	

NSN 5930-01-039-9022

Pressure Switch - Page 2 of 2

No Fiig: A048b0



Contact Voltage Rating In Volts: 480.0 ac at sea level first voltage Pressure Connector Type: Double compression, threaded internal single connection Media For Which Designed: Gas or liquid Style Designator: Rectangular w/bracket Thread Series Designator: Npt single pressure connection Shelf Life: N/a Unit Of Measure: - Demilitarization: