

View Online at <https://aerobasegroup.com/nsn/5930-01-040-0499>

Thread Class:

2a

Body Style:

Bushing/hole mounted

Overall Length:

1.875 inches

Overall Height:

1.500 inches

Overall Width:

0.750 inches

Bushing Length:

0.500 inches

Body Length:

1.250 inches

Body Width:

0.750 inches

Body Height:

0.500 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.500 inches

Actuator Height:

0.250 inches

Actuator Free Position Height:

0.750 inches

Actuator Adapter Style:

Pushbutton

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole and threaded bushing

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

8.0 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.015 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 10.000 amperes inductive dc and 10.000 amperes resistive ac

Thread Series Designator:

Unef

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0