## NSN 5930-01-040-1301

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-040-1301

## Body Style:

Bushing mounted

#### Hazardous Locations/environmental Protection:

Dustproof and corrosion resistant and shock proof

#### **Body Diameter:**

0.430 inches

#### **Bushing Length:**

0.355 inches

#### **Body Length:**

0.637 inches

#### Actuator Diameter:

0.375 inches

#### Actuator Height:

0.282 inches

#### Actuator Color:

Yellow single actuator

#### Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### Inclosure Type:

Fully enclosed

#### Mounting Method:

Threaded bushing

#### Thready Qty Per Inch (tpi):

32

## Thread Size:

0.500 inches

## Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

## Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes resistive dc and 500.000 milliamperes resistive ac

## **Precious Material And Location:**

Terminals silver and contact surfaces silver

## **Thread Series Designator:**

Un

#### **Terminal Type And Quantity:**

3 tab, solder lug

Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5930-01-040-1301

Push Switch - Page 2 of 2

Fiig: A053a0

