## NSN 5930-01-040-6274

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nen/5030-01-040-6274

view Online at https://aerobasegroup.com/hsn/5930-01-040-6274
Body Style:
Panel mounted
Overall Length:
5.000 inches
Overall Height:
1.200 inches
Overall Width:
0.960 inches
Body Width:
0.960 inches
Body Height:
1.200 inches
Case Material:
Metal
Actuator Length:
1.040 inches
Actuator Style:
Rectangular
Actuator Height:
0.140 inches
Actuator Width:
0.800 inches
Actuator Color:
Red single actuator
Illuminated Actuator Color:
Red single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
4.860 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
4 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 5.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 ampere
industrial and 4 500 areas and 4 sources.

### **Test Data Document:**

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

### **Terminal Type And Quantity:**

E tob colder lug and 12 turret

inductive ac and 1.500 amperes lamp ac

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# NSN 5930-01-040-6274

Push Switch - Page 2 of 2



Spec	ific	ation	Data:
------	------	-------	-------

81349-mil-s-22885/9 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0