## NSN 5930-01-040-6275

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-040-6275

view Offilite at https://aerobasegroup.com/hisr/0300-01-040-0270
Body Style:
Panel mounted
Overall Length:
3.250 inches
Overall Height:
1.200 inches
Overall Width:
0.960 inches
Body Width:
0.960 inches
Body Height:
1.200 inches
Case Material:
Metal
Actuator Length:
1.040 inches
Actuator Style:
Rectangular
Actuator Height:
0.140 inches
Actuator Width:
0.800 inches
Actuator Color:
Red single actuator and red single actuator
Illuminated Actuator Color:
Red single actuator and red single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
3.110 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
2 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 5.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes
inductive ac and 1.500 amperes lamp ac

## Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Terminal Type And Quantity:

5 tab solder lug and 6 turret

## NSN 5930-01-040-6275

Push Switch - Page 2 of 2



Spec	ifica	ation	Data:
------	-------	-------	-------

81349-mil-s-22885/9 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0