NSN 5930-01-040-6776

Pressure Switch - Page 1 of 2



view Online at https://aerobasegroup.com/hsn/5930-01-040-6776
Inside Diameter:
0.188 inches all connections
Overall Length:
1.312 inches
Outside Diameter:
0.203 inches all connections
Overall Height:
0.475 inches
Overall Width:
1.875 inches
Body Length:
1.000 inches
Body Height:
0.375 inches
Unthreaded Mounting Hole Diameter:
Between 0.091 inches and 0.097 inches
Longest Horizontal Distance Between Mounting Centers:
0.719 inches
Longest Vertical Distance Between Mounting Centers:
0.719 inches
Pressure Switch Type:
Differential
Mounting Method:
Base and unthreaded hole
Contact Action Stimulus:
Increase
Proof Pressure:
10.00 pounds per square inch gage
Mounting Facility Pattern:
Four position rectangular
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Quick disconnect, male
Contact Load Current Rating:
20.0 milliamperes resistive load single voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
0.50 actuation point inches of water
Contact Voltage Rating In Volts:

30.0 ac at sea level single voltage

NSN 5930-01-040-6776Pressure Switch - Page 2 of 2



Pressure Connector Type:
Barbed, unthreaded external all connections
Media For Which Designed:
Liquid
Style Designator:
Rectangular
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0