

View Online at <https://aerobasegroup.com/nsn/5930-01-040-6996>

**Hazardous Locations/environmental Protection:**

Shock resistant and vibration resistant

**Overall Length:**

Between 3.230 inches and 3.290 inches

**Overall Height:**

1.936 inches

**Overall Width:**

Between 1.120 inches and 1.180 inches

**Unthreaded Mounting Hole Diameter:**

0.100 inches single mounting facility

**Individual Section Quantity:**

4

**Longest Horizontal Distance Between Mounting Centers:**

3.060 inches single mounting facility and 3.120 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

0.890 inches single mounting facility and 0.910 inches single mounting facility

**Operating Temperature Range:**

-65.0/+85.0 degrees celsius

**Mounting Method:**

Bracket single mounting facility and unthreaded hole single mounting facility

**Actuator Type:**

Thumbwheel all actuators

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

8 all actuators

**Terminal Type:**

Printed circuit

**Contact Load Current Rating:**

125.0 milliamperes resistive load dc at sea level

**Readout Indicator Marking:**

X, y, z, xy, xxy, xyz, xyz, xyz, x 1st section

**Contact Arrangement Truth Table:**

Decimal, 1 pole - 8 positions each section

**Color:**

White each indicator marking

**Precious Material And Location:**

Contact surfaces gold

**Precious Material:**

Gold

**Style Designator:**

Rectangular inline indicating

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0