NSN 5930-01-040-7549

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-040-7549

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Overall Length:

2.844 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.438 inches single actuator

Overall Diameter:

2.375 inches

Individual Section Quantity:

1

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Cam actuated

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level

Cam Actuated Switch Contact Arrangement:

2 pole, double throw, three positions maintained each switch single section rear

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

100.0 milliamperes resistive load ac at sea level

Style Designator:

Circular, cam actuated

Thread Series Designator:

Unef single mounting facility

NSN 5930-01-040-7549

Rotary Switch - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0