

View Online at <https://aerobasegroup.com/nsn/5930-01-040-7555>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

0.511 inches

**Overall Height:**

1.402 inches

**Overall Width:**

0.866 inches

**Bushing Length:**

0.354 inches

**Body Length:**

0.511 inches

**Body Width:**

0.866 inches

**Case Material:**

Plastic

**Actuator Style:**

Round

**Actuator Diameter:**

0.115 inches

**Actuator Height:**

0.410 inches

**Actuator Position-action Relationship:**

Up position momentary and down position momentary and center position maintained

**Maximum Voltage Rating In Volts:**

115.0 ac and 29.0 dc

**Mounting Surface To Terminal End Distance:**

0.638 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

4 pole, double throw, two positions momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 5.000 amperes resistive ac

**Precious Material And Location:**

Terminals gold and contact surfaces gold

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

12 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0