NSN 5930-01-040-7842

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-040-7842
Body Style:
Hole mounted
Overall Length:
0.850 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Body Length:
0.850 inches
Body Width:
0.265 inches
Body Height:
0.359 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Length:
0.656 inches
Actuator Style:
Leaf
Actuator Width:
0.156 inches

Actuator Free Position Height:

0.400 inches

0.400 inches

Actuator Adapter Style:

Leaf

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

5.0 ounces

Actuator Movement:

Between 0.030 pretravel inches and 0.005 overtravel inches and 0.004 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac

NSN 5930-01-040-7842 Sensitive Switch - Page 2 of 2



Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0