

View Online at <https://aerobasegroup.com/nsn/5930-01-040-8066>

Inside Diameter:

0.250 inches single connection

Overall Length:

5.250 inches

Overall Height:

3.000 inches

Overall Width:

3.188 inches

Body Length:

3.000 inches

Body Height:

2.500 inches

Unthreaded Mounting Hole Diameter:

0.138 inches

Longest Horizontal Distance Between Mounting Centers:

2.625 inches

Longest Vertical Distance Between Mounting Centers:

2.438 inches

Pressure Switch Type:

Gage

Mounting Method:

Base and unthreaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

1000.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

10.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+11.00/+250.00 actuation point pounds per square inch and +10.00/+230.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Pressure Connector Type:

Double compression, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0