

View Online at <https://aerobasegroup.com/nsn/5930-01-040-8750>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Moisture resistant

Body Length:

1.188 inches

Body Width:

1.125 inches

Case Material:

Metal

Actuator Length:

1.125 inches

Actuator Style:

Rectangular

Actuator Height:

0.406 inches

Actuator Width:

1.125 inches

Actuator Color:

Amber single actuator and white single actuator

Illuminated Actuator Color:

Amber single actuator and white single actuator

Actuator Inscription:

Mult, fault/pressto, sequence single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Rfi shielding

Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.500 amperes inductive dc and 2.000 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

Terminal Type And Quantity:

4 tab, solder lug and 12 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0