

View Online at <https://aerobasegroup.com/nsn/5930-01-041-1379>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof and watertight

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

0.330 inches

Actuator Height:

0.968 inches

Actuator Free Position Height:

1.718 inches

Housing Length:

2.460 inches

Housing Width:

1.000 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

1.000 inches

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Integral

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary, two positions maintained single switch unit

Switch Release Force:

Between 3.0 ounces and 10.0 ounces

Switch Actuating Force:

Between 6.0 ounces and 20.0 ounces

Actuator Movement:

Between 0.078 pretravel inches and 0.187 overtravel inches and 0.002 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0