## NSN 5930-01-041-2996

Push Switch - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5930-01-041-2996
Body Style:
Bushing mounted
Hazardous Locations/environmental Protection:
Vibration resistant
Overall Length:
0.781 inches
Overall Height:
2.375 inches
Overall Width:
0.609 inches
Bushing Length:
0.359 inches
Body Length:
0.781 inches
Body Width:
0.609 inches
Body Height:
0.875 inches
Actuator Diameter:
0.750 inches
Actuator Height:
0.891 inches
Maximum Voltage Rating In Volts:
250.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000
amperes inductive ac and 3.000 amperes lamp ac
Thread Series Designator:
Uns
Terminal Type And Quantity:
2 turret and 4 tab, solder lug
Shelf Life:

## NSN 5930-01-041-2996

Push Switch - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A053a0