

View Online at <https://aerobasegroup.com/nsn/5930-01-041-3011>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Moisture resistant

**Body Length:**

1.188 inches

**Body Width:**

1.125 inches

**Case Material:**

Metal

**Actuator Length:**

1.125 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.406 inches

**Actuator Width:**

1.125 inches

**Actuator Color:**

White single actuator

**Illuminated Actuator Color:**

White single actuator

**Actuator Inscription:**

Lo freq/broad single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Rfi shielding

**Nonpile-up Contact Arrangement:**

4 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc and 2.500 amperes inductive dc and 2.000 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

**Terminal Type And Quantity:**

4 tab, solder lug and 12 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0