

View Online at <https://aerobasegroup.com/nsn/5930-01-041-3686>

Thread Class:

2a single pressure connection

Overall Length:

1.900 inches

Body Length:

1.250 inches

Pressure Switch Type:

Gage

Width Across Flats:

0.680 inches

Mounting Method:

Input port

Features Provided:

Tamper proof cap

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

200.00 pounds per square inch gage

Thread Size:

0.250 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Wire loop

Contact Load Current Rating:

7.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

12.00 actuation point pounds per square inch gage and 10.00 deactuation point pounds per square inch gage and 2.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Pressure Connector Type:

Flareless, threaded external single connection

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0