

View Online at <https://aerobasegroup.com/nsn/5930-01-041-6281>

Thread Class:

2a single mounting facility

Thread Length:

0.219 inches single mounting facility

Overall Length:

3.000 inches

Overall Height:

1.469 inches

Overall Width:

1.312 inches

Shaft Diameter:

0.250 inches 1st actuator

Shaft Length:

0.594 inches 2nd actuator

Nonturn Device Radius:

0.438 inches at 9: 00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 9: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section periphery

Throw Quantity:

5 each section periphery

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Dummy terminal and variable resistor

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Switch Actuator Indexing Position Quantity:

5 all actuators

Shaft Type:

Round, hollowed 1st actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section periphery

Switch Actuator Positioning Increment:

30.0 degrees all actuators

Switch Actuator Stop Device Type:

Adjustable stop all actuators

Contact Load Current Rating:

750.0 milliamperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0