

View Online at <https://aerobasegroup.com/nsn/5930-01-041-6476>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.138 inches

Overall Height:

0.676 inches

Body Diameter:

0.625 inches

Mounting Slot Width:

0.145 inches

Body Height:

0.470 inches

Distance Between Mounting Facility Centers:

0.938 inches

Temperature Sensing Element Type:

Internal sensor

Mounting Method:

Bracket and slot

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

7.2 amperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

199.00 actuation point degrees fahrenheit and 180.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

277.0 ac at sea level second voltage

Media For Which Designed:

Gas or liquid

Unpackaged Unit Weight:

4.000 grams

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Style Designator:

Disc w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0