

View Online at <https://aerobasegroup.com/nsn/5930-01-041-6485>

Thread Class:

2a single mounting facility

Thread Length:

0.500 inches single mounting facility

Hazardous Locations/environmental Protection:

Shock proof

Overall Length:

2.620 inches

First Flat Length:

0.500 inches single actuator

Flat Height:

0.219 inches single actuator

Shaft Diameter:

0.245 inches single actuator and 0.249 inches single actuator

Shaft Length:

0.500 inches single actuator

Overall Diameter:

1.875 inches

Individual Section Quantity:

2

Knob Manufacturer Code:

54294

Knob Manufacturer Part Number:

53-635

Nonturn Device Type:

Slotted bushing at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

6 each section rear

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.469 inches single mounting facility

Contact Voltage Rating In Volts:

30.0 highest dc voltage rating at sea level

Shaft Flat/slot Angular Location:

0.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

6 single actuator

Shaft Type:

Round, flatted, threaded hole single actuator

Terminal Type:

Screw

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load lowest dc voltage rating at sea level and 5.0 amperes inductive load lowest dc voltage rating at sea level and 2.0 amperes lamp load lowest dc voltage rating at sea level and 4.0 amperes motor load lowest dc voltage rating at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0