NSN 5930-01-041-6500

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-041-6500 **Body Style:** Hole mounted **Center To Center Distance Between Mounting Facilities Parallel To Length:** 0.375 inches **Body Length:** 0.781 inches **Body Width:** 0.250 inches **Body Height:** 0.356 inches **Unthreaded Mounting Hole Diameter:** 0.088 inches **Actuator Style:** Round **Actuator Free Position Height:** 0.330 inches **Maximum Voltage Rating In Volts:** 250.0 ac and 30.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Unthreaded hole **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit **Switch Release Force:** 1.0 inch-ounces **Switch Actuating Force:** Between 3.0 inch-ounces and 5.0 inch-ounces **Actuator Movement:** Between 0.020 pretravel inches and 0.003 overtravel inches and 0.004 differential inches **Contact Load Current Rating At Maximum Rated Voltage:** 5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig:

A053a0