

View Online at <https://aerobasegroup.com/nsn/5930-01-042-1290>

Inside Diameter:

0.250 inches single connection

Overall Length:

5.680 inches

Overall Height:

2.120 inches

Overall Width:

4.000 inches

Body Length:

3.000 inches

Body Height:

2.120 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

Distance Between Mounting Facility Centers:

2.750 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -35.0 degrees celsius and 90.0 degrees celsius

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Proof Pressure:

2500.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+10.00/+240.00 actuation point pounds per square inch and +8.00/+235.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

480.0 ac at sea level single voltage

Pressure Connector Type:

Gasket seal, threaded internal single connection

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0