

View Online at <https://aerobasegroup.com/nsn/5930-01-042-5167>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Oiltight

Case Material:

Metal

Actuator Style:

Round

Actuator Height:

0.625 inches

Actuator Free Position Height:

0.750 inches

Housing Height:

1.540 inches

Housing Length:

4.220 inches

Housing Width:

0.178 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.340 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.160 inches

Maximum Voltage Rating In Volts:

600.0 ac and 240.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.5 inch-ounces

Switch Actuating Force:

48.0 inch-ounces

Actuator Movement:

10.0 pretravel degrees and 5.0 overtravel degrees and 2.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

100.000 milliamperes resistive dc and 1.200 amperes resistive ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0