

View Online at <https://aerobasegroup.com/nsn/5930-01-042-5167>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Oiltight

**Case Material:**

Metal

**Actuator Style:**

Round

**Actuator Height:**

0.625 inches

**Actuator Free Position Height:**

0.750 inches

**Housing Height:**

1.540 inches

**Housing Length:**

4.220 inches

**Housing Width:**

0.178 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

2.340 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

1.160 inches

**Maximum Voltage Rating In Volts:**

600.0 ac and 240.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

4.5 inch-ounces

**Switch Actuating Force:**

48.0 inch-ounces

**Actuator Movement:**

10.0 pretravel degrees and 5.0 overtravel degrees and 2.0 differential degrees

**Contact Load Current Rating At Maximum Rated Voltage:**

100.000 milliamperes resistive dc and 1.200 amperes resistive ac

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0