

View Online at <https://aerobasegroup.com/nsn/5930-01-042-7287>

Overall Length:

4.875 inches

Overall Width:

2.875 inches

Body Length:

4.625 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Capillary Tube Length:

120.0 inches

Bulb Length:

3.000 inches

Bulb Diameter:

0.375 inches

Longest Horizontal Distance Between Mounting Centers:

2.406 inches

Shortest Horizontal Distance Between Mounting Centers:

1.750 inches

Longest Vertical Distance Between Mounting Centers:

3.281 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Operating Temperature Rating:

195.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Decrease

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

3.2 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+90.00/+165.00 actuation point degrees fahrenheit and +90.00/+165.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

550.0 ac at sea level first voltage

Media For Which Designed:

Gas or liquid

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0