Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-042-7638

Hazard	ous Locations/environmental Protection:
Dustpro	pof
Overal	Length:
6.626 ir	nches
Overal	Height:
2.906 ir	nches
Overal	Width:
2.813 ir	nches
Unthre	aded Mounting Hole Diameter:
0.221 ir	nches single mounting facility
Individ	ual Section Quantity:
4	
Knob M	Ianufacturer Code:
82121	
Knob M	Ianufacturer Part Number:
С	
Longes	st Horizontal Distance Between Mounting Centers:
2.000 ir	nches single mounting facility
Shorte	st Horizontal Distance Between Mounting Centers:
1.000 ir	nches single mounting facility
Longes	st Vertical Distance Between Mounting Centers:
2.188 ir	nches single mounting facility
Switch	Contact Basic Design:
Nonpile	-up symmetrical
Pole Q	uantity:
1 each	section rear
Throw	Quantity:
3 each	section rear
Mounti	ng Method:
Unthrea	aded hole single mounting facility
Feature	es Provided:
Actuato	r knob
Contac	t Voltage Rating In Volts:
500.0 h	ighest ac voltage rating at sea level
Mounti	ng Facility Pattern:
Isoscel	es triangle single mounting facility
Switch	Actuator Indexing Position Quantity:
3 single	e actuator
Termin	al Type:
Tab w/s	screw
Contac	t Switching Action:
Makes	before breaks 2nd section rear

## NSN 5930-01-042-7638

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

45.0 degrees single actuator

## Switch Actuator Stop Device Type:

Adjustable stop single actuator

**Contact Load Current Rating:** 

5.0 amperes resistive load highest ac voltage rating at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0