

View Online at <https://aerobasegroup.com/nsn/5930-01-042-8923>

**Hazardous Locations/environmental Protection:**

Corrosion resistant

**Body Diameter:**

0.688 inches

**Bushing Length:**

1.228 inches

**Body Length:**

1.000 inches

**Case Material:**

Metal

**Actuator Style:**

Roller plunger

**Actuator Free Position Height:**

1.863 inches

**Actuator Roller Diameter:**

0.375 inches

**Actuator Roller Width:**

0.104 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

2 pole, single throw, normally open, momentary action single switch unit

**Switch Release Force:**

64.0 ounces

**Switch Actuating Force:**

192.0 ounces

**Actuator Movement:**

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 2.500 amperes inductive dc and 4.000 amperes motor dc

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

6 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0