## NSN 5930-01-043-0684

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-043-0684

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Waterproof and dustproof and oiltight
Actuator Style:
Round
Actuator Height:
0.500 inches
Actuator Free Position Height:
2.266 inches
Housing Height:
2.500 inches
Housing Length:
7.063 inches
Housing Width:
2.281 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.625 inches
Maximum Voltage Rating In Volts:
600.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
2 two circuit, double break/double make, one position momentary single switch unit
Switch Release Force:
40.0 inch-ounces
Switch Actuating Force:
264.0 inch-ounces
Actuator Movement:
19.0 pretravel degrees and 71.0 overtravel degrees and 15.0 differential degrees
Contact Load Current Rating At Maximum Rated Voltage:
750.000 milliamperes resistive dc and 2.500 amperes resistive ac
Terminal Type And Quantity:
8 screw
Shelf Life:
N/a
Unit Of Measure:

--

## **NSN 5930-01-043-0684** Sensitive Switch - Page 2 of 2



em			

No

Fiig:

A053a0