

View Online at <https://aerobasegroup.com/nsn/5930-01-043-0684>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Waterproof and dustproof and oiltight

Actuator Style:

Round

Actuator Height:

0.500 inches

Actuator Free Position Height:

2.266 inches

Housing Height:

2.500 inches

Housing Length:

7.063 inches

Housing Width:

2.281 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.625 inches

Maximum Voltage Rating In Volts:

600.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, one position momentary single switch unit

Switch Release Force:

40.0 inch-ounces

Switch Actuating Force:

264.0 inch-ounces

Actuator Movement:

19.0 pretravel degrees and 71.0 overtravel degrees and 15.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

750.000 milliamperes resistive dc and 2.500 amperes resistive ac

Terminal Type And Quantity:

8 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0