

View Online at <https://aerobasegroup.com/nsn/5930-01-043-0704>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Corrosion resistant

**Body Diameter:**

1.000 inches

**Bushing Length:**

0.688 inches

**Body Length:**

0.980 inches

**Actuator Style:**

Roller plunger

**Actuator Free Position Height:**

Between 1.751 inches and 1.811 inches

**Actuator Roller Diameter:**

0.500 inches

**Actuator Roller Width:**

0.125 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Hermetically sealed

**Mounting Method:**

Threaded bushing

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action single switch unit

**Switch Release Force:**

64.0 ounces

**Switch Actuating Force:**

144.0 ounces

**Actuator Movement:**

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc and 2.000 amperes inductive dc and 4.000 amperes motor dc

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

2 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0