

View Online at <https://aerobasegroup.com/nsn/5930-01-043-0704>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Corrosion resistant

Body Diameter:

1.000 inches

Bushing Length:

0.688 inches

Body Length:

0.980 inches

Actuator Style:

Roller plunger

Actuator Free Position Height:

Between 1.751 inches and 1.811 inches

Actuator Roller Diameter:

0.500 inches

Actuator Roller Width:

0.125 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded bushing

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action single switch unit

Switch Release Force:

64.0 ounces

Switch Actuating Force:

144.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.000 amperes inductive dc and 4.000 amperes motor dc

Thread Series Designator:

Unef

Terminal Type And Quantity:

2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0