

View Online at <https://aerobasegroup.com/nsn/5930-01-043-0706>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Weatherproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.997 inches and 1.003 inches

Body Width:

0.390 inches

Case Material:

Metal

Unthreaded Mounting Hole Diameter:

Between 0.140 inches and 0.144 inches

Actuator Length:

Between 0.539 inches and 0.549 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

0.640 inches

Actuator Roller Diameter:

Between 0.209 inches and 0.213 inches

Actuator Roller Width:

Between 0.154 inches and 0.158 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 inch-ounces

Criticality Code Justification:

Feat

Switch Actuating Force:

1.5 inch-ounces

Actuator Movement:

0.040 pretravel inches and 0.075 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 1.000 amperes inductive dc and 2.000 amperes lamp dc

Special Features:

Must be procured iaw grumman aerospace corp. Dwg gs838s and is utilized in a critical application on a f-14a aircraft

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0