

View Online at <https://aerobasegroup.com/nsn/5930-01-043-1974>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

8.750 inches

Shaft Diameter:

0.250 inches 1st actuator

Shaft Length:

0.625 inches 1st actuator

Overall Diameter:

1.562 inches

Nonturn Device Radius:

0.531 inches at 10: 00 o'clock

Individual Section Quantity:

6

Nonturn Device Type:

Tab at 10: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical and nonpile-up nonsymmetrical

Pole Quantity:

1 5th section rear

Throw Quantity:

5 5th section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

17 single actuator

Shaft Type:

Round, hollowed 1st actuator

Criticality Code Justification:

Feat

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes 2nd section rear

Switch Actuator Positioning Increment:

20.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Special Features:

Weapon system essential

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0