

View Online at <https://aerobasegroup.com/nsn/5930-01-043-2400>

Thread Class:

2a

Body Style:

Bushing mount

Overall Length:

0.575 inches

Overall Height:

2.020 inches

Overall Width:

0.535 inches

Bushing Length:

0.470 inches

Body Length:

0.575 inches

Body Width:

0.535 inches

Case Material:

Plastic

Actuator Style:

Rectangular

Actuator Height:

0.810 inches

Actuator Width:

0.300 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Maximum Voltage Rating In Volts:

28.0 dc and 115.0 ac

Mounting Surface To Terminal End Distance:

0.740 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, three positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 2.000 amperes inductive ac and 1.000 amperes lamp ac

Precious Material And Location:

Contacts silver and terminal surfaces gold

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0